



Our extra heavy duty PVC spiral reinforced conduit offers excellent durability and crush resistance and is ideal for applications where hosing down of machinery is essential due to its smooth, wipe clean surface.

Constructed entirely from PVC, G-Series offers complete protection against corrosion and can be easily cut with a sharp knife, leaving a clean edge to work with and making installation of fittings quick and easy.

Technical Details

Temperature Range: -10°C to +60°C

Material: Thermoplastic resin with polyvinyl chloride (PVC)

Colour: Black

Flame resistance: Self-extinguishing within 30 seconds (UL94V0)

Ingress Protection: IP65

Other Information: CE

UV Resistant

Manufactured to BS EN 61386

Product Code	Trade Size	Internal Diameter	External Diameter	Bending Radius	Coil Size
G12-30M	12mm	10.0mm	14.0mm	50mm	30m
G16-30M	16mm	12.0mm	16.3mm	60mm	30m
G20-30M	20mm	16.0mm	20.0mm	80mm	30m
G25-30M	25mm	22.0mm	26.8mm	110mm	30m
G32-30M	32mm	28.0mm	33.5mm	140mm	30m



PVC Spiral Straight Fittings

- Locknuts included
- 2 Part Fitting (Body & Shell)
- IP65

Product Code	Conduit Size	Thread Size	Pack Size
AF16	16mm	M16 x 1.5mm	10
AF20	20mm	M20 x 1.5mm	10
AF25	25mm	M25 x 1.5mm	10
AF32	32mm	M32 x 1.5mm	10



PVC Spiral 90deg Elbow Fittings

- Locknuts included
- 3 part fitting (Shell, Olive, Body)
- IP65

Product Code	Conduit Size	Thread Size	Pack Size
AF16E	16mm	M16 x 1.5mm	10
AF20E	20mm	M20 x 1.5mm	10
AF25E	25mm	M25 x 1.5mm	10
AF32E	32mm	M32 x 1.5mm	10